






W: studiomasterprofessional.com





AiR 24

Professional Mixing Consoles



Overview

The AiR 24 is a 24 channel Mixing Console with dual multi effects processor, designed for live, front-of-house touring and installation applications.







W: studiomasterprofessional.com






Key Features

• High quality Dual Effects Prossor.



• 100mm faders.










W: studiomasterprofessional.com





All Features




- 24 Channel Mixer (20 Mic/Line 2 Stereo Inputs).
- Built-in Dual Multi Effect Processor.
- 3-band EQ with mid-sweep on mono inputs and 2-band EQ on stereo inputs...
- Insert On Mono Channel.
- 3 AUX Channels (1 Pre, 2 Post).
- Stereo AUX Return.
- Mix & Group Routing on each channel.
- 4 Sub Group out with individual output.
- 100mm faders.
- PFL switch on each channel.
- 100Hz Low cut switch on each channel.
- +48V Phantom supply split global from 1-12 and 17-24 channels.
- Peak & Mute LED per channel.
- 2-track RCA record output.
- Headphones & Monitor outputs with level control.
- 2-track RCA Input with level control.
- Balanced XLR & Jack Master Output







W: studiomasterprofessional.com





@studiomasterprofessional

Technical Specifications

Parameter	Specifications
Nominal Gain (Mic/Line/Stereo Line)	60dB/40dB/20dB
Max Gain (Mic/Line/Stereo Line)	80dB/60dB/40dB
Input Levels Sensitivity	
Mic (Gain Min/Gain Max)	-10dBu / -60dBu
Line (Gain Min /Gain Max)	+10dBu / -40dBu
Stereo Line (Gain Min /Gain Max)	+10dBu / -20dBu
Input Impedence	

Mic Input	1.5 K Balanced
Line input	20K (Balanced) /10K (Unbalanced)
Main Output & Group Output (Nominal / Max)	+0dBu (0.775V RMS) / +20dBu (7.75V RMS)
Frequency Response	20Hz to 20KHz (+0/-1 dB)
Total Harmonic Distortion	< 0.02%
Signal to Noise Ratio	-80dB
Clip indication	5dB prior to true clip

Equalisation

Mono Mic [Treble/Mid(with sweep)/Bass]	±16dB @ 12KHz/140Hz-3KHz/80 Hz
Stereo Mic/Line (Treble/Bass)	±16dB @ 12KHz/80Hz
EFX & USB	2 x 16EFX (EFX1 & EFX2)
Phantom supply	+48V (Separate Selection for 1-12 & 17-24 Channels)
Power supply	150V 250V AC/50Hz (External Power supply)
Dimensions (W x D x H) mm	680 x 520 x 130
Net Weight (Kg)	12.5







W: studiomasterprofessional.com





Dimensions










W: studiomasterprofessional.com





Support

For sales, support, pricing and availability:


Email: info@audioplus-india.com Telephone: 022-42869000 / 001 WhatsApp: +91-8879028079

(Monday to Saturday between 10:00 a.m to 6:00 p.m.)

Contact Us:

http://www.studiomasterprofessional.com/home/contact







For after-sales service and support: Email: sales.support@audioplus-india.com Telephone: 022-42869010 / 49 / 57

Subscribe to our Channel





















* Product design and specifications are subject to change without notice.

Studiomaster Professional is a registered trademark of Audioplus in India. © Copyright Audioplus, 2008. All rights reserved. Any unauthorised reproduction or use of logos, images or design elements is strictly prohibited by law. No part of the compilation may be reproduced in any manner or translated without written permission.

Code: Rev001 / SMP AiR 24 Datasheet / June 2022

